



Advanced Validation Labs, Inc.
 17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S7200AP (Adams Pass)	Test Result: Pass

Leveraged System(s): HNS7200AP,HNS7200APL,S7200AP,S7200APF,S7200APL

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RD8L/16MEI	RDIMM	1.2V	16GB	2Gx72	2666	19	H	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A1G8SA-075:E	8Gb 1024Mx8bit 1804			IDT B		(1024Mx8)*2*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	S22021	S22020
System S/N	QSAD63905310 / Low	QSAD63905435 / High
Board Rev. (PBA)	G94286-304	
CPU Type	Xeon PHI 7250 / 1.4 GHz	
Chipset	C612	
BIOS	01.02.0041	
BMC / ME	01.01.10452 / 03.01.03.018	
FUR/SDR	1.25	
OS	Linux CentOS 7.3	
Test Tool	iLvss, MCELog	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max Loading	HVDD Hot Pass
4. Memory Stress		HVDD Cold Pass
5. Memory Stress		LVDD Hot Pass
6. Memory Stress		LVDD Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	06/07/2018	AVL A#	U181145	AVL W/O	WF1184
Comments:							

Test Results

4C						
Maximum Loading						
Start Date		6/1/2018				
DIMM Voltage		1.22v				
DIMM VPP		2.64v				
DIMM	S/N	A	B	C	D	
CPU1 A1	45-0021	P	P	P	P	
CPU1 B1	45-0022	P	P	P	P	
CPU1 C1	45-0023	P	P	P	P	
CPU1 D1	46-0023	P	P	P	P	
CPU2 E1	46-0024	P	P	P	P	
CPU2 F1	46-0025	P	P	P	P	

4C						
Maximum Loading						
Start Date		6/1/2018				
DIMM Voltage		1.16v				
DIMM VPP		2.422v				
DIMM	S/N	E	F	G	H	
CPU1 A1	45-0021	P	P	P	P	
CPU1 B1	45-0022	P	P	P	P	
CPU1 C1	45-0023	P	P	P	P	
CPU1 D1	46-0023	P	P	P	P	
CPU2 E1	46-0024	P	P	P	P	
CPU2 F1	46-0025	P	P	P	P	