



Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S7200AP (Adams Pass)	Test Result: Pass

Leveraged System(s): HNS7200AP,HNS7200APL,S7200AP,S7200APF,S7200APL

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM29RS8/8HDR	RDIMM	1.2V	8GB	1Gx72	2933	21	D	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
SK Hynix	H5AN8G8NDJR-WMC	8Gb	1024Mx8bit	2013	Rambus	B0	(1024Mx8)*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	S22021	S22020
System S/N	QSAD63905310 / Low	QSAD63905435 / High
Board Rev. (PBA)	G94286-304	
CPU Type	Xeon PHI 7250 / 1.4 GHz	
Chipset	C612	
BIOS	01.02.0041	
BMC / ME	01.01.10452 / 03.01.03.018	
FUR/SDR	1.25	
OS	Linux CentOS 7.3	
Test Tool	iLvss, MCELog	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max Loading	HVDD Hot Pass
4. Memory Stress		HVDD Cold Pass
5. Memory Stress		LVDD Hot Pass
6. Memory Stress		LVDD Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	03/30/2021	AVL A#	U201538	AVL W/O	WF8275
Comments:							

Test Results

4C Maximum Loading						
Start Date	3/22/2021					
DIMM Voltage	1.22v					
DIMM VPP	2.64v					
DIMM	S/N	A	B	C	D	
CPU1 A1	0020	P	P	P	P	P
CPU1 B1	0021	P	P	P	P	P
CPU1 C1	0022	P	P	P	P	P
CPU1 D1	0023	P	P	P	P	P
CPU2 E1	0024	P	P	P	P	P
CPU2 F1	0025	P	P	P	P	P

4C Maximum Loading							
Start Date	3/22/2021						
DIMM Voltage	1.16v						
DIMM VPP	2.422v						
DIMM	S/N	E	F	G	H		
CPU1 A1	0014	P	P	P	P	P	P
CPU1 B1	0015	P	P	P	P	P	P
CPU1 C1	0016	P	P	P	P	P	P
CPU1 D1	0017	P	P	P	P	P	P
CPU2 E1	0018	P	P	P	P	P	P
CPU2 F1	0019	P	P	P	P	P	P