



Advanced Validation Labs, Inc.
17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S7200AP (Adams Pass)	Test Result: Pass

Leveraged System(s): HNS7200AP,HNS7200APL,S7200AP,S7200APF,S7200APL

Modules Information

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KVR24R17D4/32L	RDIMM	1.2V	32GB	4Gx72	2400	17	B	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A2G4PM-083E:A	8Gb	2048Mx4bit	1630/1632	Montage	1	(2048Mx4)*2*72		

Leveraged Memory Modules

Vendor	Type	Voltage	CL	Speed
1 Kingston	KVR24R17D4K4/128L	RDIMM	1.2V	17 2400
2				
3				
4				
5				
6				

System Configuration

SETUP	System #1	System #2
AVL S/N	S22021	S22020
System S/N	QSAD63905310 / Low	QSAD63905435 / High
Board Rev. (PBA)	G94286-304	
CPU Type	Xeon PHI 7250 / 1.4 GHz	
Chipset	C612	
BIOS / Date	01.02.0041 / 02-23-2017	
BMC / ME	01.01.10452 / 03.01.03.018	
FUR/SDR	1.25	
OS	Linux CentOS 7.3	
Test Tool	iLvss, MCELog	

Testing Summary

Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max Loading	HVDD/HVPP Hot Pass
4. Memory Stress		HVDD/HVPP Cold Pass
5. Memory Stress		LVDD/LVPP Hot Pass
6. Memory Stress		LVDD/LVPP Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:

Completed by:	Andy Chang	Completion Date:	03/30/2017	AVL A#	A11872 / A11873	AVL W/O	WD7668 / WD7669
---------------	------------	------------------	------------	--------	-----------------	---------	-----------------

Comments:

Test Results

4C						
Maximum Loading						
Start Date		3/27/2017				
DIMM Voltage		1.22v				
DIMM VPP		2.64v				
DIMM	S/N	A	B	C	D	
CPU1 A1	S22709	P	P	P	P	
CPU1 B1	S22710	P	P	P	P	
CPU1 C1	S22711	P	P	P	P	
CPU1 D1	S22701	P	P	P	P	
CPU2 E1	S22702	P	P	P	P	
CPU2 F1	S22703	P	P	P	P	

4C						
Maximum Loading						
Start Date		3/27/2017				
DIMM Voltage		1.16v				
DIMM VPP		2.422v				
DIMM	S/N	E	F	G	H	
CPU1 A1	S22712	P	P	P	P	
CPU1 B1	S22713	P	P	P	P	
CPU1 C1	S22714	P	P	P	P	
CPU1 D1	S22704	P	P	P	P	
CPU2 E1	S22705	P	P	P	P	
CPU2 F1	S22706	P	P	P	P	