



### Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: <b>Intel S2600BP (Buchanan Pass)</b>	Test Result: <b>Pass</b>

Leveraged System(s): BBS2600BPB,BBS2600BPQ,BBS2600BPS,HNS2600BPB,HNS2600BPB24,HNS2600BPQ,HNS2600BPQ24,HNS2600BPS,HNS2600BPS24,S2600BP

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM29RS8/8MEI	RDIMM	1.2V	8GB	1Gx72	2933	21	D1	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A1G8SA-062E:E	8Gb 1024Mx8bit 1904			IDT C1		(1024Mx8)*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	H170047-003	H170047-004
System S/N	QSBP83210875	QSBP83210819
Board Rev. (PBA)	H87926-553	
CPU Type	Intel CLX 2.20 GHz	
Chipset	Intel 62X Series	
BIOS	01.0261	
BMC / ME	1.83 / 04.01.03.237	
FUR/SDR	1.38	
OS	Windows Server 2016 Standard	
Test Tool	iWVSS 2.8.0, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot Pass
4. Memory Stress		HVDD Cold Pass
5. Memory Stress		LVDD Hot Pass
6. Memory Stress		LVDD Cold Pass
Note:		

#### Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	05/23/2019	AVL A#	U191207	AVL W/O	WF2326
Comments:							

#### Test Results

4C Minimum Loading				
Start Date		5/8/2019		
DIMM Voltage		1.22v / 1.16v		
DIMM	S/N	A	B	C D
CPU1 A1	07-001	P	P	P P
CPU1 A2				
CPU1 B1	07-002	P	P	P P
CPU1 C1	07-003	P	P	P P
CPU1 D1	07-004	P	P	P P
CPU1 D2				
CPU1 E1	07-005	P	P	P P
CPU1 F1	07-006	P	P	P P
CPU2 G1	98-001	P	P	P P
CPU2 G2				
CPU2 H1	98-002	P	P	P P
CPU2 I1	98-003	P	P	P P
CPU2 J1	98-004	P	P	P P
CPU2 J2				
CPU2 K1	98-005	P	P	P P
CPU2 L1	98-006	P	P	P P

4C Maximum Loading				
Start Date		05/08/19		
DIMM Voltage		1.22v / 1.16v		
DIMM	S/N	A	B	C D
CPU1 A1	07-001	P	P	P P
CPU1 A2	07-002	P	P	P P
CPU1 B1	07-003	P	P	P P
CPU1 C1	07-004	P	P	P P
CPU1 D1	07-005	P	P	P P
CPU1 D2	07-006	P	P	P P
CPU1 E1	07-007	P	P	P P
CPU1 F1	07-008	P	P	P P
CPU2 G1	98-001	P	P	P P
CPU2 G2	98-002	P	P	P P
CPU2 H1	98-003	P	P	P P
CPU2 I1	98-004	P	P	P P
CPU2 J1	98-005	P	P	P P
CPU2 J2	98-006	P	P	P P
CPU2 K1	98-007	P	P	P P
CPU2 L1	98-008	P	P	P P