



**Advanced Validation Labs, Inc.**  
17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



**Intel PCSD Server Memory Compatibility Test Certificate**

Test System: <b>Intel S2600BP (Buchanan Pass)</b>	Test Result: <b>Pass</b>
---	--------------------------

Leveraged System(s): BBS2600BPB,BBS2600BPQ,BBS2600BPS,HNS2600BPB,HNS2600BPB24,HNS2600BPQ,HNS2600BPQ24,HNS2600BPS,HNS2600BPS24,S2600BP

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM32RS4/16MRR	RDIMM	1.2V	16GB	2Gx72	3200	22	C3	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A2G4SA-062E:R	8Gb	2048Mx4bit	2130	Rambus	B0	(2048Mx4)x2*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	H170047-003	H170047-004
System S/N	QSBP83210875	QSBP71001654
Board Rev. (PBA)	H87926-553	H87926-501
CPU Type	XeonGold 5215M/2.50 GHz Xeon Gold 6252 / 2.1 GHz	
Chipset	Intel 62X Series	
BIOS	02.01.5010	02.01.0012
BMC / ME	2.48 / 04.01.04.381	
FUR/SDR	1.45	
OS	Windows Server 2016 Standard	
Test Tool	iWVSS 2.9.2, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	<b>Done</b>
2. SPD Check	DIMM SPD content check for JEDEC compliance	<b>Pass</b>
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot <b>Pass</b>
4. Memory Stress		HVDD Cold <b>Pass</b>
5. Memory Stress		LVDD Hot <b>Pass</b>
6. Memory Stress		LVDD Cold <b>Pass</b>
Note:		

**Memory Module Image**



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	4/22/2022	AVL A#	U221235	AVL W/O	WG1301
Comments:							

**Test Results**

4C Minimum Loading					
Start Date		3/29/2022			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	0001	P	P	P	P
CPU1 A2					
CPU1 B1	0002	P	P	P	P
CPU1 C1	0003	P	P	P	P
CPU1 D1	0004	P	P	P	P
CPU1 D2					
CPU1 E1	0005	P	P	P	P
CPU1 F1	0006	P	P	P	P
CPU2 G1	0007	P	P	P	P
CPU2 G2					
CPU2 H1	0008	P	P	P	P
CPU2 I1	0009	P	P	P	P
CPU2 J1	0010	P	P	P	P
CPU2 J2					
CPU2 K1	0011	P	P	P	P
CPU2 L1	0012	P	P	P	P

4C Maximum Loading					
Start Date		03/29/22			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	0001	P	P	P	P
CPU1 A2	0002	P	P	P	P
CPU1 B1	0003	P	P	P	P
CPU1 C1	0004	P	P	P	P
CPU1 D1	0005	P	P	P	P
CPU1 D2	0006	P	P	P	P
CPU1 E1	0007	P	P	P	P
CPU1 F1	0008	P	P	P	P
CPU2 G1	0009	P	P	P	P
CPU2 G2	0010	P	P	P	P
CPU2 H1	0011	P	P	P	P
CPU2 I1	0012	P	P	P	P
CPU2 J1	0013	P	P	P	P
CPU2 J2	0014	P	P	P	P
CPU2 K1	0015	P	P	P	P
CPU2 L1	0016	P	P	P	P