



Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S2600BP (Buchanan Pass)	Test Result: Pass


Leveraged System(s): BBS2600BPB,BBS2600BPQ,BBS2600BPS,HNS2600BPB,HNS2600BPB24,HNS2600BPQ,HNS2600BPQ24,HNS2600BPS,HNS2600BPS24,S2600BP

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM32RS4/32HCR	RDIMM	1.2V	32GB	4Gx72	3200	22	C3	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
SK Hynix	H5ANAG4NCJR-XNC	16Gb	4096Mx4bit	2203	Rambus	B0	(4096Mx4)*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	H170047-003	H170047-004
System S/N	QSBP83210875	QSBP71001654
Board Rev. (PBA)	H87926-553	H87926-501
CPU Type	XeonGold 5215M/2.50 GHz Xeon Gold 6252 / 2.1 GHz	
Chipset	Intel 62X Series	
BIOS	02.01.5010	02.01.0012
BMC / ME	2.48 / 04.01.04.381	
FUR/SDR	1.45	
OS	Windows Server 2016 Standard	
Test Tool	iWVSS 2.9.2, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot Pass
4. Memory Stress		HVDD Cold Pass
5. Memory Stress		LVDD Hot Pass
6. Memory Stress		LVDD Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	05/04/2022	AVL A#	U221238	AVL W/O	WG1334
Comments:							

Test Results

4C Minimum Loading					
Start Date		5/2/2022			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	0029	P	P	P	P
CPU1 A2					
CPU1 B1	0030	P	P	P	P
CPU1 C1	0031	P	P	P	P
CPU1 D1	0032	P	P	P	P
CPU1 D2					
CPU1 E1	0033	P	P	P	P
CPU1 F1	0034	P	P	P	P
CPU2 G1	0035	P	P	P	P
CPU2 G2					
CPU2 H1	0036	P	P	P	P
CPU2 I1	0037	P	P	P	P
CPU2 J1	0038	P	P	P	P
CPU2 J2					
CPU2 K1	0039	P	P	P	P
CPU2 L1	0040	P	P	P	P

4C Maximum Loading					
Start Date		05/02/22			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	0013	P	P	P	P
CPU1 A2	0014	P	P	P	P
CPU1 B1	0015	P	P	P	P
CPU1 C1	0016	P	P	P	P
CPU1 D1	0017	P	P	P	P
CPU1 D2	0018	P	P	P	P
CPU1 E1	0019	P	P	P	P
CPU1 F1	0020	P	P	P	P
CPU2 G1	0021	P	P	P	P
CPU2 G2	0022	P	P	P	P
CPU2 H1	0023	P	P	P	P
CPU2 I1	0024	P	P	P	P
CPU2 J1	0025	P	P	P	P
CPU2 J2	0026	P	P	P	P
CPU2 K1	0027	P	P	P	P
CPU2 L1	0028	P	P	P	P