



Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S2600BP (Buchanan Pass)	Test Result: Pass


Leveraged System(s): BBS2600BPB,BBS2600BPQ,BBS2600BPS,HNS2600BPB,HNS2600BPB24,HNS2600BPQ,HNS2600BPQ24,HNS2600BPS,HNS2600BPS24,S2600BP

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM32RS8/16MFR	RDIMM	1.2V	16GB	2Gx72	3200	22	D1	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A2G8SA-062E:F	16Gb	2048Mx8bit	2202	Rambus	B0	(2048Mx8)*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	H170047-003	H170047-004
System S/N	QSBP83210875	QSBP71001654
Board Rev. (PBA)	H87926-553	H87926-501
CPU Type	XeonGold 5215M/2.50 GHz	Xeon Gold 6252 / 2.1 GHz
Chipset	Intel 62X Series	
BIOS	02.01.5010	02.01.0012
BMC / ME	2.48 / 04.01.04.381	
FUR/SDR	1.45	
OS	Windows Server 2016 Standard	
Test Tool	iWVSS 2.9.2, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot Pass
4. Memory Stress		HVDD Cold Pass
5. Memory Stress		LVDD Hot Pass
6. Memory Stress		LVDD Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	9/9/2022	AVL A#	U221545	AVL W/O	WG2104
Comments:							

Test Results

4C Minimum Loading				
Start Date		8/24/2022		
DIMM Voltage		1.22v / 1.16v		
DIMM	S/N	A	B	C D
CPU1 A1	001	P	P	P P
CPU1 A2				
CPU1 B1	002	P	P	P P
CPU1 C1	003	P	P	P P
CPU1 D1	004	P	P	P P
CPU1 D2				
CPU1 E1	005	P	P	P P
CPU1 F1	006	P	P	P P
CPU2 G1	007	P	P	P P
CPU2 G2				
CPU2 H1	008	P	P	P P
CPU2 I1	009	P	P	P P
CPU2 J1	010	P	P	P P
CPU2 J2				
CPU2 K1	011	P	P	P P
CPU2 L1	012	P	P	P P

4C Maximum Loading				
Start Date		08/24/22		
DIMM Voltage		1.22v / 1.16v		
DIMM	S/N	A	B	C D
CPU1 A1	001	P	P	P P
CPU1 A2	002	P	P	P P
CPU1 B1	003	P	P	P P
CPU1 C1	004	P	P	P P
CPU1 D1	005	P	P	P P
CPU1 D2	006	P	P	P P
CPU1 E1	007	P	P	P P
CPU1 F1	008	P	P	P P
CPU2 G1	009	P	P	P P
CPU2 G2	010	P	P	P P
CPU2 H1	011	P	P	P P
CPU2 I1	012	P	P	P P
CPU2 J1	013	P	P	P P
CPU2 J2	014	P	P	P P
CPU2 K1	015	P	P	P P
CPU2 L1	016	P	P	P P