

Server Memory Compatibility Test Certificate

Test System: **Supermicro X10SRI-F** Test Result: **Pass**

Leveraged System(s): X10SRL-F, X10SRH-CF, X10SRH-CLN4F, X10SRG-F, X10SRW-F, X10SRA, X10SRA-F, X10SRM-F, X10SRM-TF, X10SRG-F, X10SRW-F

Module Specifications

Rev. Rev. 05/16/19

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM24RD4/32HDI	RDIMM	1.2v	32GB	4096Mx72	2400	17-17-17	B2	2
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code		Register Vendor / Rev.		DIMM Composition			
SK Hynix	H5AN8G4NDJR-XNC	8Gb	2048Mx4	2008	IDT	B1	(2048Mx4)*72		


System Configuration

SETUP	System Information
AVL S/N	SV2269
System S/N	0M148S016129
Board Rev. (PBA)	1.01
CPU Type	Intel E5-2650 v4 (BDW) x1
Chipset	Intel C612
BIOS / Date	3.1c /5/19/2019
BMC / ME	1.89/3.0.5.422
FRU/SDR	N/A
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7 /Memtest86+

Testing Summary

Test Items	Test Description			Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS			Done
2. SPD Check	DIMM SPD content check for JEDEC compliance			Pass
3. Reset Cycle	Max Load	Room	200 Loops	Pass
4. Memory Stress - Memtest86+		Room	2 Loops	Pass
5. Memory Stress-Stressapptest		40°C	24Hrs	Pass
Note:				

Memory Module Image



AVL USE ONLY:

Completed by:	Van Nguyen	Completion Date:	10/20/2020	AVL A#	U201685	AVL W/O	WF7939
Comments:							