

**Server Memory Compatibility Test Certificate**

Test System: **Supermicro X10DRi-LN4+**

Test Result: **Pass**

Leveraged System(s): X10DRi-T4+, X10DRC-T4+ / X10DRC-LN4+, X10DRU-i+ / X10DRG-OT+-CPU, X10DRG-O+-CPU, X10DRU-i+, X10DSC+

**Module Specifications**

Rev. 1/13/2015

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RS4/16HCI	RDIMM	1.20V	16GB	2Gx72	2666	19	C2	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Sk Hynix	H5AN8G4NCJR-WMC	8Gb 2048Mx4bit 1920			IDT B1		(2048Mx4)*72		

**System Configuration**


SETUP	System Information
AVL S/N	SV2272
System S/N	VM148S014767
Board Rev. (PBA)	1.01
CPU Type	Intel E5-2650 v4 (BDW) x2
Chipset	Intel C612
BIOS / Date	3.1a / 04/27/2019
BMC / ME	1.85/3.06.267
FRU/SDR	N/A
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7 / Memtest86+

**Testing Summary**

Test Items	Test Description		Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS		<b>Done</b>
2. SPD Check	DIMM SPD content check for JEDEC compliance		<b>Pass</b>
3. Reset Cycle	Max Load	Room 200 Loops	<b>Pass</b>
4. Memory Stress - Memtest86+		2 Loops	<b>Pass</b>
5. Memory Stress-Stressapptest		40°C 24Hrs	<b>Pass</b>

Note:

**Memory Module Image**



**AVL USE ONLY:**

Completed by:	Van Nguyen	Completion Date:	7/29/2019	AVL A#	U191276	AVL W/O	WF2741
Comments:							