

Server Memory Compatibility Test Certificate

Test System: **Supermicro X11SRA** Test Result: **Pass**

Leveraged Board(s) / System(s): X11SRA, X11SRA-F, X11SRA-RF, SYS-5039A-I

Module Specifications

Rev. 05/16/19

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RS4/32MEI	RDIMM	1.2V	32GB	4096Mx72	2666	19-19-19	C3	1
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code	Register Vendor / Rev.	DIMM Composition					
Micron Technology Inc.	MT40A4G4JC-062E:E	16Gb	4096Mx4	2024	IDT	B1	(4096Mx4)*72		

System Configuration

SETUP	System Information
AVL S/N	h190330-01
System S/N	7902
Board Rev. (PBA)	1.02
CPU Type	Intel Xeon W-2225
Chipset	C422
BIOS / Date	2.0a /02/10/20
BMC / ME	1.21 / 11.11.60.1561
FRU/SDR	n/a
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7 / Memtest86+

Testing Summary

Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Reset Cycle	Max Load Room	200 Loops Pass
4. Memory Stress - Memtest86+		2 Loops Pass
5. Memory Stress-Stressapptest		40°C 24Hrs Pass
Note:		

Memory Module Image



AVL USE ONLY:

Completed by:	Van Nguyen	Completion Date:	9/15/2020	AVL A#	U201576	AVL W/O	WF7451
Comments:							