

Server Memory Compatibility Test Certificate

Test System: **Supermicro X11SPW-TF (System SYS-5029P-WTR)** Test Result: **Pass**

Leveraged Board(s) / System(s): X11SPW-TF, X11SPW-CTF, X11SPM-TPF, X11SPM-TF, X11SPM-F, X11SPG-TF, SYS-1019P-WTR, SYS-5019P-WT, SYS-5019P-WTR, SYS-5029P-WTR, SYS-5019GP-TT, SYS-1019GP-TT

Module Specifications

Rev. 3/27/2018

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RS8/8MEI	RDIMM	1.2V	8GB	1Gx72	2666	19	D1	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Kingston	MT40A1G8SA-075:E	8Gb 1024Mx8bit 1802			IDT B1		(1024x8)*72		


System Configuration

SETUP	System Information
AVL S/N	H180199-001
System S/N	N80205
Board Rev. (PBA)	1.02
CPU Type	Intel Xeon Gold 6130(SKX) x2
Chipset	Skylake
BIOS / Date	2.0b /2/26/18
BMC / ME	n/a
FRU/SDR	n/a
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7

Testing Summary

Test Items	Test Description		Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS		Done
2. SPD Check	DIMM SPD content check for JEDEC compliance		Pass
3. Reset Cycle	1 DIMM Per Channel when applicable		Pass
4a. Memory Stress	DIMM Loading per spec	45°C	24 Hours Pass
4c. Reset Cycle			200 loops per config Pass
Note:			

Memory Module Image



AVL USE ONLY:

Completed by:	Van Nguyen	Completion Date:	6/12/2018	AVL A#	U181067	AVL WO	WF1167
---------------	------------	------------------	-----------	--------	---------	--------	--------

Comments: