

Server Memory Compatibility Test Certificate

Test System: **Supermicro X11SPW-TF (System SYS-5029P-WTR)** Test Result: **Pass**

Leveraged Board(s) / System(s): X11SPW-TF, X11SPW-CTF, X11SPM-TPF, X11SPM-TF, X11SPM-F, X11SPG-TF, SYS-1019P-WTR, SYS-5019P-WT, SYS-5019P-WTR, SYS-5029P-WTR, SYS-5019GP-TT, SYS-1019GP-TT

Module Specifications

Rev. 3/27/2018

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM29RD8/16MEI	RDIMM	1.2V	16GB	2Gx72	2933	21	E2	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code	Register Vendor / Rev.	DIMM Composition					
Micron	MT40A1G8SA-062E:E	8Gb	1024Mx8bit	1904	IDT	C1	(2048Mx8)*72		


System Configuration

SETUP	System Information
AVL S/N	H180199-001
System S/N	N80205
Board Rev. (PBA)	1.02
CPU Type	Intel Xeon Gold 6252(PLCX)
Chipset	C621
BIOS / Date	3.0b /3/04/19
BMC / ME	n/a
FRU/SDR	n/a
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7/Memtest 86+

Testing Summary

Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Reset Cycle	Max Load Room	200 Loops Pass
4. Memory Stress - Memtest86+		2 Loops Pass
5. Memory Stress-Stressapptest	40°C	24Hrs Pass
Note:		

Memory Module Image



AVL USE ONLY:

Completed by:	Van Nguyen	Completion Date:	7/29/2019	AVL A#	U191196	AVL WO	WF2433
---------------	------------	------------------	-----------	--------	---------	--------	--------

Comments: