

Server Memory Compatibility Test Certificate

Test System: **Supermicro X10SRI-F** Test Result: **Pass**

Leveraged System(s): X10SRL-F, X10SRH-CF, X10SRH-CLN4F, X10SRG-F, X10SRW-F, X10SRA, X10SRA-F, X10SRM-F, X10SRM-TF, X10SRG-F, X10SRW-F

Module Specifications

Rev. Rev. 05/16/19

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank	
Kingston	KSM29RS8/8HDR	RDIMM	1.2v	8GB	1024Mx72	2933	21-21-21	D1	1	
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code		Register Vendor / Rev.		DIMM Composition				
SK Hynix	H5AN8G8NDJR-WMC	8Gb		1024Mx8		2013		Rambus	B0	(1024Mx8)*72


System Configuration

SETUP	System Information
AVL S/N	SV2269
System S/N	0M148S016129
Board Rev. (PBA)	1.01
CPU Type	Intel E5-2650 v4 (BDW) x1
Chipset	Intel C612
BIOS / Date	3.1c /5/19/2019
BMC / ME	1.89/3.0.5.422
FRU/SDR	N/A
OS	Ubuntu 16.04 LTS
Test Tool	Stressapptest 1.0.7 /Memtest86+

Testing Summary

Test Items	Test Description		Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS		Done
2. SPD Check	DIMM SPD content check for JEDEC compliance		Pass
3. Reset Cycle	Max Load	Room	Pass
4. Memoy Stress - Memtest86+		200 Loops	Pass
5. Memory Stress-Stressapptest		40°C	Pass
Note:			

Memory Module Image



AVL USE ONLY:

Completed by:	Van Nguyen	Completion Date:	9/23/2020	AVL A#	U201538	AVL W/O	WF7794
Comments:							