



## Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



### Intel PCSD Server Memory Compatibility Test Certificate

Test System: **Intel S2600ST (SawTooth Pass)**

Test Result: **Pass**

Leveraged System(s): BBS2600STQ,S2600ST,S2600STB,S2600STQ

#### Modules Information

DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RS4/16MEI	RDIMM	1.2V	16GB	2Gx72	2666	19	C	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A2G4SA-075:E	8Gb	2048Mx4bit	1802	IDT	B	(2048Mx4)*72		


#### System Configuration

SETUP	System #1	System #2
AVL S/N	H170061-001	H170061-003
System S/N	FWSP71420190	FWSP71420061
Board Rev. (PBA)	J17012-400	
CPU Type	Platinum 8170 M / 2.10 GHz	
Chipset	C610	
BIOS	0X.01.0108	
BMC / ME	1.43 / 04.00.04.294	
FUR/SDR	1.28	
OS	Windows Server 2016 Standard	
Test Tool	iWVSS 2.7.0, SELViewer, Syscfg, WinPIRA	

#### Testing Summary

Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot
4. Memory Stress		HVDD Cold
5. Memory Stress		LVDD Hot
6. Memory Stress		LVDD Cold
Note:		

#### Memory Module Image



#### AVL USE ONLY:

Completed by:	Andy Chang	Completion Date:	02/16/2018	AVL A#	U181063	AVL W/O	WF0826
---------------	------------	------------------	------------	--------	---------	---------	--------

Comments:

Test Results

4C					
Minimum Loading					
Start Date		2/12/2018			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	63-0001	P	P	P	P
CPU1 A2					
CPU1 B1	63-0002	P	P	P	P
CPU1 C1	63-0003	P	P	P	P
CPU1 D1	63-0004	P	P	P	P
CPU1 D2					
CPU1 E1	63-0005	P	P	P	P
CPU1 F1	63-0006	P	P	P	P
CPU2 G1	64-0001	P	P	P	P
CPU2 G2					
CPU2 H1	64-0002	P	P	P	P
CPU2 I1	64-0003	P	P	P	P
CPU2 J1	64-0004	P	P	P	P
CPU2 J2					
CPU2 K1	64-0005	P	P	P	P
CPU2 L1	64-0006	P	P	P	P

4C					
Maximum Loading					
Start Date		02/12/18			
DIMM Voltage		1.22v / 1.16v			
DIMM	S/N	A	B	C	D
CPU1 A1	63-0006	P	P	P	P
CPU1 A2	63-0007	P	P	P	P
CPU1 B1	63-0008	P	P	P	P
CPU1 C1	63-0009	P	P	P	P
CPU1 D1	63-0010	P	P	P	P
CPU1 D2	63-0011	P	P	P	P
CPU1 E1	63-0012	P	P	P	P
CPU1 F1	63-0013	P	P	P	P
CPU2 G1	64-0006	P	P	P	P
CPU2 G2	64-0007	P	P	P	P
CPU2 H1	64-0008	P	P	P	P
CPU2 I1	64-0009	P	P	P	P
CPU2 J1	64-0010	P	P	P	P
CPU2 J2	64-0011	P	P	P	P
CPU2 K1	64-0012	P	P	P	P
CPU2 L1	64-0013	P	P	P	P