



Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S2600TP (Taylor Pass)	Test Result: Pass


Leveraged System(s): S2600TPNR, HNS2600TP, HNS2600TP24R, HNS2600TP24SR, HNS2600TPF, HNS2600TPFR, HNS2600TPNR, HNS2600TPR, S2600TP, S2600TPF, S2600TPFR, S2600TPR

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM24RD8/16HCL	RDIMM	1.2V	16GB	2Gx72	2400	17	E	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
SK Hynix	H5AN8G8NCJR-WMC	8Gb	1024Mx8bit	1914	IDT	C0	(1024Mx8)*2*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	SU9574	SU9575
System S/N	BQTP42700005 / LVPP	BQTP42700200 / HVPP
Board Rev. (PBA)	H26989-202	
CPU Type	E5-2690 v4 / 2.60 GHz	
Chipset	C610	
BIOS	01.01.0024	
BMC / ME	1.50 / 043	
FUR/SDR	1.17	
OS	Windows Server 2012 R2	
Test Tool	iWVSS 2.7.0, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD/HVPP Hot Pass
4. Memory Stress		HVDD/HVPP Cold Pass
5. Memory Stress		LVDD/LVPP Hot Pass
6. Memory Stress		LVDD/LVPP Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	01/24/2020	AVL A#:	U191266	AVL W/O:	WF2594
Comments:							

Test Results

4C Minimum Loading						
Start Date		1/6/2020				
DIMM Voltage		1.22v / 1.16v				
DIMM VPP		2.64v / 2.422v				
DIMM	S/N	A	B	C	D	
CPU1 A1	66-001	P	P	P	P	
CPU1 A2						
CPU1 B1	66-002	P	P	P	P	
CPU1 B2						
CPU1 C1	66-003	P	P	P	P	
CPU1 C2						
CPU1 D1	66-004	P	P	P	P	
CPU1 D2						
CPU2 E1	67-001	P	P	P	P	
CPU2 E2						
CPU2 F1	67-002	P	P	P	P	
CPU2 F2						
CPU2 G1	67-003	P	P	P	P	
CPU2 G2						
CPU2 H1	67-004	P	P	P	P	
CPU2 H2						

4C Maximum Loading						
Start Date		01/06/20				
DIMM Voltage		1.22v / 1.16v				
DIMM VPP		2.64v / 2.422v				
DIMM	S/N	A	B	C	D	
CPU1 A1	66-001	P	P	P	P	
CPU1 A2	66-002	P	P	P	P	
CPU1 B1	66-003	P	P	P	P	
CPU1 B2	66-004	P	P	P	P	
CPU1 C1	66-005	P	P	P	P	
CPU1 C2	66-006	P	P	P	P	
CPU1 D1	66-007	P	P	P	P	
CPU1 D2	66-008	P	P	P	P	
CPU2 E1	67-001	P	P	P	P	
CPU2 E2	67-002	P	P	P	P	
CPU2 F1	67-003	P	P	P	P	
CPU2 F2	67-004	P	P	P	P	
CPU2 G1	67-005	P	P	P	P	
CPU2 G2	67-006	P	P	P	P	
CPU2 H1	67-007	P	P	P	P	
CPU2 H2	67-008	P	P	P	P	