



Advanced Validation Labs, Inc.

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S2600TP (Taylor Pass)	Test Result: Pass

Leveraged System(s): S2600TPNR, HNS2600TP, HNS2600TP24R, HNS2600TP24SR, HNS2600TPF, HNS2600TPFR, HNS2600TPNR, HNS2600TPR, S2600TP, S2600TPF, S2600TPFR, S2600TPR

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KSM26RD8L/16MEI	RDIMM	1.2V	16GB	2Gx72	2666	19	H	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A1G8SA-075:E	8Gb 1024Mx8bit 1804			IDT B		(1024Mx8)*2*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	SU9574	SU9575
System S/N	BQTP42700005 / LVPP	BQTP42700200 / HVPP
Board Rev. (PBA)	H26989-202	
CPU Type	E5-2690 v4 / 2.60 GHz	
Chipset	C610	
BIOS	01.01.0024	
BMC / ME	01.50.10802 / 03.01.03.043	
FUR/SDR	1.17	
OS	Windows Server 2012 R2	
Test Tool	iWVSS 2.7.0, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD/HVPP Hot Pass
4. Memory Stress		HVDD/HVPP Cold Pass
5. Memory Stress		LVDD/LVPP Hot Pass
6. Memory Stress		LVDD/LVPP Cold Pass
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	05/31/2018	AVL A#	U181145	AVL W/O	WF1182
Comments:							

Test Results

4C						
Minimum Loading						
Start Date		5/21/2018				
DIMM Voltage		1.22v / 1.16v				
DIMM VPP		2.64v / 2.422v				
DIMM	S/N	A	B	C	D	
CPU1 A1	45-0025	P	P	P	P	
CPU1 A2						
CPU1 B1	45-0005	P	P	P	P	
CPU1 B2						
CPU1 C1	45-0006	P	P	P	P	
CPU1 C2						
CPU1 D1	45-0007	P	P	P	P	
CPU1 D2						
CPU2 E1	46-0001	P	P	P	P	
CPU2 E2						
CPU2 F1	46-0002	P	P	P	P	
CPU2 F2						
CPU2 G1	46-0003	P	P	P	P	
CPU2 G2						
CPU2 H1	46-0004	P	P	P	P	
CPU2 H2						

4C						
Maximum Loading						
Start Date		05/21/18				
DIMM Voltage		1.22v / 1.16v				
DIMM VPP		2.64v / 2.422v				
DIMM	S/N	A	B	C	D	
CPU1 A1	45-0017	P	P	P	P	
CPU1 A2	45-0018	P	P	P	P	
CPU1 B1	45-0019	P	P	P	P	
CPU1 B2	45-0020	P	P	P	P	
CPU1 C1	45-0021	P	P	P	P	
CPU1 C2	45-0022	P	P	P	P	
CPU1 D1	45-0023	P	P	P	P	
CPU1 D2	45-0024	P	P	P	P	
CPU2 E1	46-0009	P	P	P	P	
CPU2 E2	46-0010	P	P	P	P	
CPU2 F1	46-0011	P	P	P	P	
CPU2 F2	46-0012	P	P	P	P	
CPU2 G1	46-0013	P	P	P	P	
CPU2 G2	46-0014	P	P	P	P	
CPU2 H1	46-0015	P	P	P	P	
CPU2 H2	46-0016	P	P	P	P	