



**Advanced Validation Labs, Inc.**

17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: <b>Intel S2600TP (Taylor Pass)</b>	Test Result: <b>Pass</b>


Leveraged System(s): S2600TPNR, HNS2600TP, HNS2600TP24R, HNS2600TP24SR, HNS2600TPF, HNS2600TPFR, HNS2600TPNR, HNS2600TPR, S2600TP, S2600TPF, S2600TPFR, S2600TPR

Modules Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KVR24R17D8/16l	RDIMM	1.2V	16GB	2Gx72	2400	17	E	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Micron	MT40A1G8PM-083E:A	8Gb	1024Mx8bit	1612	Montage	D00G	(1024Mx8)*2*72		

Leveraged Memory Modules						
Vendor	Type	Voltage	CL	Speed		
1 Kingston	KVR24R17D8K4/64l	RDIMM	1.2V	17	2400	
2						
3						
4						
5						
6						

System Configuration		
SETUP	System #1	System #2
AVL S/N	SU9574	SU9575
System S/N	BQTP42700005 / LVPP	BQTP42700200 / HVPP
Board Rev. (PBA)	H26989-202	
CPU Type	E5-2690 v4 / 2.60 GHz	
Chipset	C610	
BIOS / Date	01.01.0015 / 01-28-2016	
BMC / ME	01.43.9685 / 03.01.03.021	
FUR/SDR	1.14	
OS	Windows Server 2012 R2	
Test Tool	iWVSS 2.6.1, SELViewer, Syscfg, WinPIRA	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	<b>Done</b>
2. SPD Check	DIMM SPD content check for JEDEC compliance	<b>Pass</b>
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD/HVPP Hot <b>Pass</b>
4. Memory Stress		HVDD/HVPP Cold <b>Pass</b>
5. Memory Stress		LVDD/LVPP Hot <b>Pass</b>
6. Memory Stress		LVDD/LVPP Cold <b>Pass</b>
Note:		



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	07/05/16	AVL A#	A11353	AVL W/O	WD6059
Comments:							

Test Results

4C					
Minimum Loading					
Start Date		6/14/2016			
DIMM Voltage		1.22v / 1.16v			
DIMM VPP		2.64v / 2.422v			
DIMM	S/N	A	B	C	D
CPU1 A1	SZ2653	P	P	P	P
CPU1 A2					
CPU1 B1	SZ2654	P	P	P	P
CPU1 B2					
CPU1 C1	SZ2655	P	P	P	P
CPU1 C2					
CPU1 D1	SZ2656	P	P	P	P
CPU1 D2					
CPU2 E1	SZ2657	P	P	P	P
CPU2 E2					
CPU2 F1	SZ2658	P	P	P	P
CPU2 F2					
CPU2 G1	SZ2659	P	P	P	P
CPU2 G2					
CPU2 H1	SZ2660	P	P	P	P
CPU2 H2					

4C					
Maximum Loading					
Start Date		06/14/16			
DIMM Voltage		1.22v / 1.16v			
DIMM VPP		2.64v / 2.422v			
DIMM	S/N	A	B	C	D
CPU1 A1	SZ2653	P	P	P	P
CPU1 A2	SZ2654	P	P	P	P
CPU1 B1	SZ2655	P	P	P	P
CPU1 B2	SZ2656	P	P	P	P
CPU1 C1	SZ2657	P	P	P	P
CPU1 C2	SZ2658	P	P	P	P
CPU1 D1	SZ2659	P	P	P	P
CPU1 D2	SZ2660	P	P	P	P
CPU2 E1	SZ2678	P	P	P	P
CPU2 E2	SZ2679	P	P	P	P
CPU2 F1	SZ2680	P	P	P	P
CPU2 F2	SZ2681	P	P	P	P
CPU2 G1	SZ2682	P	P	P	P
CPU2 G2	SZ2683	P	P	P	P
CPU2 H1	SZ2684	P	P	P	P
CPU2 H2	SZ2685	P	P	P	P