



AMD EXPO™ Technology Memory Profile Self-Certification Report

[General Module Information]	
Module Manufacturer:	KINGSTON
Module Part Number:	KF564C32BBEAK2-64 (Kit of 2) KF564C32BBEA-32 (x2) KF564C32BWEAK2-64 (Kit of 2) KF564C32BWEA-32 (x2)
Serial Number:	N/A
Module Revision:	1
Module Size:	32 GBytes
Ranks per channel:	2
JEDEC Memory Speed:	DDR5-4800
Module Type:	Unbuffered DIMM (UDIMM)
SDRAM Manufacturer:	SK Hynix
DRAM Stepping:	A
Error Check/Correction:	None

[AMD EXPO Profile Support]	
AMD EXPO Version	1
Profile 0 Enabled	Yes
Profile 0 DIMMs per Channel	1
Profile 1 Enhanced Block Enabled	No
Profile 1 Enabled	Yes
Profile 1 DIMMs per Channel	1
Profile 1 Enhanced Block Enabled	No

[EXPO Profile 0 Voltage]	
SDRAM VDD (V)	1.4 V
SDRAM VDDQ (V)	1.4 V
SDRAM VPP (V)	1.80 V



[EXPO Profile 0 Timing]		
DDR Data Rate MT/S	6400 MT/s	
tCK (ps / nCK)	312 ps	
tCAS (ps / nCK)	10000 ps	32 nCK
tRCD (ps / nCK)	12187 ps	39 nCK
tRP (ps / nCK)	12187 ps	39 nCK
tRAS (ps / nCK)	25000 ps	80 nCK
tRC (ps / nCK)	37187 ps	119 nCK
tRW (ps / nCK)	30000 ps	96 nCK
tRFC1 (ns)	295 ns	
tRFC2 (ns)	160 ns	
tRFCsb (ns)	130 ns	

[EXPO Profile 0 Enhanced Timing]		
tRRD_L (ps / nCK)	N/A	
tCCD_L (ps / nCK)	N/A	
tCCD_L_WR (ps / nCK)	N/A	
tCCD_L_WR2 (ps / nCK)	N/A	
tFAW (ps / nCK)	N/A	
tWTR_L (ps / nCK)	N/A	
tWTR_S (ps / nCK)	N/A	
tRTP (ps / nCK)	N/A	

[EXPO Profile 1 Voltage]	
SDRAM VDD (V)	1.4 V
SDRAM VDDQ (V)	1.4 V
SDRAM VPP (V)	1.80 V



[EXPO Profile 1 Timing]		
DDR Data Rate MT/S	6000 MT/s	
tCK (ps / nCK)	333 ps	
tCAS (ps / nCK)	10000 ps	30 nCK
tRCD (ps / nCK)	12000 ps	36 nCK
tRP (ps / nCK)	12000 ps	36 nCK
tRAS (ps / nCK)	26666 ps	80 nCK
tRC (ps / nCK)	38666 ps	116 nCK
tRW (ps / nCK)	30000 ps	90 nCK
tRFC1 (ns)	295 ns	
tRFC2 (ns)	160 ns	
tRFCsb (ns)	130 ns	

[EXPO Profile 1 Enhanced Timing]		
tRRD_L (ps / nCK)	N/A	
tCCD_L (ps / nCK)	N/A	
tCCD_L_WR (ps / nCK)	N/A	
tCCD_L_WR2 (ps / nCK)	N/A	
tFAW (ps / nCK)	N/A	
tWTR_L (ps / nCK)	N/A	
tWTR_S (ps / nCK)	N/A	
tRTP (ps / nCK)	N/A	

[EXPO Tested Platforms]	[BIOS Version]	[Processor]	[ProcODT2]	[RTT2]	[DrvStr2]
ASRock - X670E Taichi	2.10	Ryzen™ 5 7600X	AUTO	AUTO	AUTO

Notes:

- The list of tested platforms (which includes the Motherboard, BIOS, and Processor configurations) is not an exhaustive list of supported configurations. It is solely a set of tested configurations to demonstrate AMD EXPO™ profile viability on actual hardware.*
- ProcODT, RTT, and DrvStr values per configuration, Auto, or selected value.*